

# KRI 450 C (Coil)

FOR QUICK AND EFFICIENT CABLE COILING



## FEATURES

- Suitable even for short cable lengths starting at 1.5 m
- Small and compact cable coils for cable diameters up to 18 mm

For the CBP-Version the operating mode depends on the dimensions and weight of the cable coil and the breaking load of the rubber cord.

## TECHNICAL DATA

Performance	KRI 450 C	KRI 450 CB	KRI 450 CBP
Coil inner diameter Manual mode Automatic mode	min. 120 mm	min. 120 mm	min. 110 mm min. 110 mm
Coil outer diameter Manual mode Automatic mode	max. 390 mm	max. 390 mm	max. 390 mm max. 390 mm
Coil height	max. 110 mm	max. 110 mm	max. 105 mm
Cable diameter (flexible cable)	max. 18 mm	max. 18 mm	approx. 4 mm - 18 mm
Coil weight	approx. 40 Kg	approx. 40 Kg	approx. 20 Kg
Control system	PLC and LCD operator Terminal		
Interfaces	Synchronization with several types of prefeeding systems and cable processing machines		
Speed	Coiling speed synchronized with cable processing machine		
Power supply	230 VAC / 10 AT	230 VAC / 10 AT	230 VAC / 10 AT
Pneumatic	6 bar	6 bar	6 bar
Revolution	max. 310 min.-1	max. 310 min.-1	max. 310 min.-1
Weight	approx. 120 kg	approx. 190 kg	approx. 250 kg
Dimension (L x W x H)	600 x 795 x 1184 mm	1422 x 795 x 1300 mm	1800 x 795 x 1750 mm

### LOCATION SWITZERLAND

**Ramatech Systems AG** . Hohenrainstrasse 36 . CH - 6280 Hochdorf  
Phone: +41 41 914 26 26 . E-Mail: info@ramatech.ch

### LOCATION GERMANY

**Ramatech Systems GmbH**. Messerschmittstraße 30 . D - 89231 Neu-Ulm  
Phone: +49 731 40 199 200 . E-Mail: info@ramatech.de